

FTXP-M(9) + RXP-M

# Comfora

## Ideell for kjøling på soverommet

- › Sesong effektivitet verdier opp til A++ i kjøling
- › Ved å velge et R-32-produkt, reduseres den miljømessige påvirkningen med 68 % sammenlignet med R-410A. Dette fører direkte til lavere energiforbruk takket være den høye energieffektiviteten
- › Talestyring via Google Home og Amazon Alexa



More details and final information can be found by scanning or clicking the QR codes.



FTXM-M9



RXP-M

Efficiency data		FTXP + RXP		25M9 + 25M		35M9 + 35M	
Cooling capacity	Min./Nom./Max.	kW		1.3/2.50/3.0		1.3/3.50/4.0	
Heating capacity	Min./Nom./Max.	kW		1.30/3.00/4.00		1.30/4.00/4.80	
Power input	Cooling	Min./Nom./Max.	kW	0.31/0.65/0.72		0.29/1.01/1.30	
	Heating	Min./Nom./Max.	kW	0.25/0.69/0.95		0.29/1.00/1.29	
Space cooling	Energy efficiency class			A <sup>++</sup>			
	Capacity	Pdesign	kW	2.50		3.50	
	SEER			6.92		6.62	
	Annual energy consumption		kWh/a	126		186	
Space heating (Average climate)	Energy efficiency class			A <sup>++</sup>			
	Capacity	Pdesign	kW	2.40		2.80	
	SCOP/A			4.61		4.64	
	Annual energy consumption		kWh/a	728		845	
Nominal efficiency	EER			3.83		3.49	
	COP			4.36		4.02	
	Annual energy consumption		kWh	326		505	
	Energy labeling Directive Cooling/Heating			A/A			
Indoor unit		FTXP		25M9		35M9	
Dimensions	Unit	HeightxWidthxDepth	mm	286x770x225			
Weight	Unit		kg	8.50		9.00	
Air filter	Type			Removable / washable			
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/High	m <sup>3</sup> /min		4.2/5.8/7.7/9.7	
		Heating	Silent operation/ Low/Medium/High	m <sup>3</sup> /min		5.2/6.4/8.1/10.4	
Sound power level	Cooling		dBA	55		58	
	Heating		dBA	55		58	
Sound pressure level	Cooling	Silent operation/Low/High	dBA	19/26/40		20/27/43	
	Heating	Silent operation/Low/High	dBA	21/28/40		21/29/40	
Outdoor unit		RXP		25M		35M	
Dimensions	Unit	HeightxWidthxDepth	mm	550x658x275			
Weight	Unit		kg	26		28	
Sound power level	Cooling		dBA	60		62	
Sound pressure level	Cooling	Nom.	dBA	46		48	
	Heating	Nom.	dBA	47		48	
Operation range	Cooling	Ambient	Min.~Max.	°CDB		-10~-48	
	Heating	Ambient	Min.~Max.	°CWB		-15~-18	
Refrigerant	Type			R-32			
	GWP			675.0			
Piping connections	Charge		kg/TCO2Eq	0.55/0.37		0.70/0.48	
	Liquid	OD	mm	6.4			
	Gas	OD	mm	9.5			
	Piping length OU - IU	Max.	m	20			
	Additional refrigerant charge		kg/m	0.02 (for piping length exceeding 10m)			
Level difference IU - OU	Max.	m	12				
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50 /220-240			
Current - 50Hz	Maximum fuse amps (MFA)		A	16			